

Heavy-Duty Conventional

Prediluted, 50/50, Heavy-Duty Universal Precharged Antifreeze/Coolant

Industry Standards

This heavy-duty universal antifreeze/coolant meets the following industry specifications:

- ASTM D3306
(automotive/light-duty)
- ASTM D4985
(heavy-duty diesel/low silicate)
- ASTM D6210/11
(fully formulated and precharged)
- TMC of ATA RP 329/330*
- TMC of ATA RP203A

**The Maintenance Council of the American Trucking Assoc. Antifreeze also meets the non-phosphate requirements of European OEM's and non-silicate requirements of Japanese OEM's*

Contact Information

Antifreeze Recycling Incorporated
46991 Mindy Street #2
Tea, SD. 57064
1888-328-9959
www.cleanandgreen.com

Our Prediluted Heavy-Duty Universal Antifreeze is ready to add to your vehicle cooling system; no further dilution is necessary. It is a non-silicate, non-phosphate formulation that contains the initial charge of supplemental coolant additive (SCA) and a minimum of 1200 ppm Nitrite (as NO₂). It provides outstanding protection from cavitation erosion/corrosion in water pumps and wet sleeve cylinder liners, as well as excellent overall corrosion protection. In addition, this ethylene glycol-based Heavy-Duty, Prediluted Coolant contains an advanced additive inhibitor system to provide broader range protection than most coolants; a full range inhibitors protect all cooling system metals and year-round protection against freeze-ups, boil-overs and corrosion under extreme conditions. It includes ingredients to disperse minor oil leakage, prevent fouling and control hot surface scaling and will not damage auto finishes or rubber parts.

In automobiles, light trucks, SUV's, vans and other light duty applications, this product will provide a service life in excess of 5 years or 150,000 miles. In heavy-duty diesel applications (in which a formal monitoring and maintenance program is in place) it can provide a service life of 300,000 miles with the addition of our heavy-duty supplemental coolant additive as needed.

PHYSICAL PROPERTIES

Antifreeze Glycols	mass %	48.0 min.
Corrosion Inhibitors	mass %	1.1
Water	mass %	49.0 max.
Flash Point	°F	None
Weight per gallon at 60° F-16° C	lbs.	8.9 min.
Silicates	mass %	< 250 ppm

% Antifreeze	Freezing Point		Boiling Point*	
	°F	°C	°F	°C
40%	-12 max	-24 max	260 min	126 min
50%	-34 max	-36 max	226 min	107 min
70%	-90 max	-67 max	270 min	135 min

**Boiling point shown using conventional 15 psi radiator cap.*

Used antifreeze coolant in most states is not hazardous unless it contains more than 5 ppm of lead. We recommend that spent coolant never be disposed of by dumping into a storm sewer or onto the ground. Instead, contact your local municipality for instructions on where to and how to properly dispose of this coolant and protect our environment.

Heavy-Duty Universal Precharged 50/50 Antifreeze Coolant

Product Data Sheet

Characteristic	Specification	Company Typical	ASTM Method
Chloride	33 ppm, max.		D3634
Specific gravity, 60/60°F	1.065 min		D1122
Nitrite	1200 ppm min		D5827
Boiling Point, 50% V/V	226°F/107°C min.		D1120
Freezing Point, 50% V/V	-34°F/-37°C min.		D1177
Effect on engine or vehicle finish	No effect		--
Ash content, mass %	2.5 max.		D1119
pH, 50% V/V	7.5-11.0		D1287
Reserve alkalinity*	None specified	5 min.	D1121
Water mass %	None specified	49.0 max.	D1123
Color	Distinctive	OEM Green	--
Effect on nonmetals	No adverse effect		--
Storage stability	None specified	> 1 year	--
Foaming	150 mi vol., max. 5 sec. break, max.		D1881

**Reserve alkalinity (RA) is a term used to indicate the amount of alkaline inhibitors present in an antifreeze formulation. It is incorrect to relate a high RA with high-quality antifreeze. Present, state-of-the-art antifreeze formulations contain many new inhibitors which give added protection to certain metals but do not raise the RA numbers.*

The purchaser hereby waives all guarantees and warranties and all other liabilities, expressed or implied, arising by law or liabilities therefore, expressed or implied, arising by law or otherwise, including without limitation, all obligations and liabilities with respect to loss of use, revenue or profit, or indirect or consequential damages, and any implied warranty of fitness for a particular purpose or of merchantability, or that any information, data or products can be used without infringing patents of third parties. Purchaser agrees to limit its warranty to its customers so as not to increase WEBA Technology Corp's liability beyond that set forth herein and indemnifies and holds harmless WEBA Technology Corp from any liability.

